

BUILDING DAMAGE ASSESSMENT

Wen Dazhi, BSc, PhD

PE, PE(Geo), AC(Geo), CE, MICE, MIEAust, CPEng

BUILDING DAMAGE ASSESSMENT

- Damage categories
- Basis of damage assessment
- Staged design approach and design assumptions
- Case studies of buildings on mixed foundations
- Conclusions

GeoSS 10112009 2

DAMAGE CATEGORIES

Three broad categories that affect:

- 1) Visual appearance or aesthetics;
- 2) Serviceability or function; and
- 3) Stability.

GeoSS 10112009 3

DAMAGE CATEGORIES

Category	Typical crack width (mm)	Effects
Negligible	0.1mm	Hairline cracks only
V. Slight	<1mm	Damage mainly to internal wall finishes.
Slight	<5mm	Doors & windows may stick slightly
Moderate	5 – 15mm or several >3mm	Doors and windows sticking. Service pipes may fracture. Weather tightness impaired.
Severe	15 to 25mm	Windows and door frames distorted. Walls leaning, some loss of bearing in beams. Service pipes disrupted.
V. Severe	>25mm	Beams lose bearing, walls require shoring. Windows broken with distortion. Danger of instability.

GeoSS 10112009 4

DAMAGE CATEGORIES

Category	Typical crack width (mm)	Repair
Negligible	0.1mm	Hairline cracks only
V. Slight	<1mm	Can be easily treated during normal decoration
Slight	<5mm	Can be easily filled. Some repainting may be necessary
Moderate	5 – 15mm or several >3mm	Patching by a mason. Repainting and replacement of a small amount of brickwork.
Severe	15 to 25mm	Extensive repair works involving breaking-out and replacing sections of walls.
V. Severe	>25mm	Major repairing work involving partial or complete rebuilding.

GeoSS 10112009 5

AS2870 DAMAGE CLASSIFICATION FOR WALLS

Description of typical damage and required repair	Approximate crack width limit	Damage category
Hairline cracks	< 0.1mm	0
Fine cracks which do not need repair	< 1mm	1
Cracks noticeable but easily filled. Doors and windows stick slightly.	< 5mm	2
Cracks can be repaired and possibly a small amount of wall will need to be replaced. Doors and windows stick. Service pipes can fracture. Weather tightness often impaired.	5mm to 15mm (or a number of cracks 3mm or more in one group)	3
Extensive repair work involving breaking-out and replacing sections of walls, especially over doors and windows. Window and door frames distort. Walls lean or bulge noticeably, some loss of bearing in beams. Service pipes disrupted.	15mm to 25mm but also depends on number of cracks	4

GeoSS 10112009 6

AS2870 - DAMAGE CLASSIFICATION FOR CONCRETE FLOORS

Description of typical damage	Approximate crack width limit in floor	Change in offset	Damage category
Hairline cracks, insignificant movement of slab from level.	< 0.3mm	<1/375	0
Fine but noticeable cracks. Slab reasonably level.	< 1mm	<1/300	1
Distinct cracks. Slab noticeably curved or changed in level.	< 5mm	<1/200	2
Wide cracks. Obvious curvature or change in level.	5mm to 15mm (or a number of cracks 3mm or more in one group)	1/200 to 1/120	3
Gaps in slab. Disturbing curvature or change in level.	15mm to 25mm but also depends on number of cracks	>1/120	4

AS2870 Residential slabs and footings - construction

GeoSS 10112009 7

DAMAGE CATEGORIES

- Category 2 - Slight: Results from within the structure itself or associated with ground movement.
- Category 3 - Moderate and above: Usually associated with ground movement.

GeoSS 10112009 8

DAMAGE CATEGORIES

- Not economic to restrict to no damage.
- Typically allow up to 'slight damage' for most structures.
- Restrict to 'very slight damage' for buildings of historical or architectural significance, such as heritage buildings.


GeoSS 10112009 9

BASIS OF BUILDING DAMAGE ASSESSMENT


- Criterion for onset of visible cracking:
Limiting tensile strain.
- Local strain at onset of cracking much smaller than limiting tensile strain.

GeoSS 10112009 10

MODES OF MOVEMENT - NOT DAMAGING



UNIFORM
SETTLEMENT



UNIFORM TILT


GeoSS 10112009 11

RIGID BODY TILT




GeoSS 10112009 12

MODES OF MOVEMENT - DAMAGING



BENDING/SHEAR




HORIZONTAL
EXTENSION

GeoSS 10112009 13

MODES OF MOVEMENT - DAMAGING

**BENDING
AND
SHEAR
STRAINS
THAT
CAUSE
DAMAGE**



GeoSS 10112009 14


LIMITING TENSILE STRAIN VS DAMAGE CATEGORIES FOR MASONRY BUILDINGS

Limiting tensile strain (%)	Damage Class	Typical crack width (mm)
0.0 - 0.05	Negligible	<0.1
0.05 - 0.075	Very Slight	<1.0
0.075 - 0.15	Slight	<5.0
0.15 - 0.3	Moderate	<15
>0.3	Severe to Very Severe	>15

GeoSS 10112009 15

BENDING AND DIAGONAL STRAIN

Beam (E/G
= 2.6 for
masonry
structure)
Undergoing
Hogging
with Neutral
Axis at
Bottom
Edge




GeoSS 10112009 16

TOTAL CALCULATED STRAINS

- Horizontal strain and the bending strain
- Horizontal strain combined with diagonal strain using a Mohr's circle of strain.

GeoSS 10112009 17

INTERACTION DIAGRAM, Δ/L , ϵ_h & L/H



**DAMAGE CATEGORY CHART FOR L/H=1,
HOGGING MODE
AFTER BURLAND (1995)**

GeoSS 10112009 18

STAGED ASSESSMENT OF BUILDINGS

- Stage 1 - if settlement $< 10\text{mm}$,
- slope $< 1:500$
➔ Negligible damage
- Stage 2 - Assume 'green field conditions', building stiffness not considered, if tensile strain $< 0.15\%$
➔ Slight damage ('conservative')

GeoSS 10112009 19

STAGED ASSESSMENT OF BUILDINGS

- Stage 3 - Detailed assessment, considering stiffness of building and three dimensional effects of tunnelling and excavation

GeoSS 10112009 20

ASSUMPTIONS FOR STAGE 2

- Building simply follows the 'green field' settlement.
- Building is made of masonry.
- Settlements due to consolidation are even, and do not induce bending or horizontal strain.
- First two assumptions are considered 'conservative' i.e. they over-predict strain and damage.

GeoSS 10112009 21

STAGE 3 ASSESSMENT

- Refinement of Stage 2 assessment.
- Foundation details are considered.
 - Ground beams will reduce horizontal extension to a negligible value.
 - Piles will reduce settlements and bending strains.
 - Continuous foundations, e.g. strip footings or rafts are less prone to damaging differential settlements.

GeoSS 10112009 22

STAGE 3 ASSESSMENT

- Effects of soil-structure interaction: building stiffness will modify 'Green Field' settlements, typically making them wider and flatter.

GeoSS 10112009 23

BUILDING DAMAGE ASSESSEMENT SUMMARY SHEET

Summary

Sheet

Project/ Contract Number	
Name of Building:	
Address:	
Description of Structure:	
Description of Foundations	
Drawings available	YES/NO
Result of Preliminary Assessment	
Maximum settlement:	
Maximum slope:	
Second stage assessment required	YES/NO
Result of Second Stage Assessment	
Maximum settlement:	
Maximum ground slope:	
Maximum tensile strain:	
Detailed evaluation required	YES/NO
Detailed Assessment attached	YES/NO
Protection measures needed	YES/NO
Protection measures proposed:	



GeoSS 10112009 24

BUILDING DAMAGE ASSESSMENT

- The theory works well in buildings on uniform foundations.
- Reliance should not be placed on theoretical assessment alone.
- Careful inspection of buildings should be carried out. There would be tell-tale signs that indicate problems in the buildings.
- Detailed structural assessment will be necessary for those buildings.

GeoSS 10112009 25

CONSOLIDATION SETTLEMENTS - COMMON ASSUMPTIONS

- Consolidation settlements are generally relatively uniform if the depth and compressibility of the soft soils are uniform.
- If uniform, consolidation settlements do not cause tensile strain and do not cause damage.
- Consolidation settlements commonly assumed to have negligible effect.

GeoSS 10112009 26

CASE STUDIES OF BUILDINGS ON MIXED FOUNDATION

- For buildings on mixed foundations or founded over varying depths of soft clay, the common assumptions:
 - That it is conservative to assume that the building moves with the ground
 - That consolidation settlements do not induce significant differential settlement or tensile strain


ARE NOT APPLICABLE

GeoSS 10112009 27

FOOCHOW METHODIST CHURCH



GeoSS 10112009 28

FOOCHOW METHODIST CHURCH




GeoSS 10112009 29

FOOCHOW METHODIST CHURCH





GeoSS 10112009 30



FOOCHOW METHODIST CHURCH


GeoSS 10112009 31

FOOCHOW METHODIST CHURCH




GeoSS 10112009 32

FOOCHOW METHODIST CHURCH




GeoSS 10112009 33

FOOCHOW METHODIST CHURCH




GeoSS 10112009 34

FOOCHOW METHODIST CHURCH



GeoSS 10112009 35

FOOCHOW METHODIST CHURCH



Moderate to Severe damage (12mm crack) at 15mm settlement, before excavation started

GeoSS 10112009 36


FOOCHOW METHODIST CHURCH



Computer Room


GeoSS 10112009 37

FOOCHOW METHODIST CHURCH



GeoSS 10112009 38

FOOCHOW METHODIST CHURCH



GeoSS 10112009 39


FOOCHOW METHODIST CHURCH



Junction of Sunday School and Kindergarten

GeoSS 10112009 40

FOOCHOW METHODIST CHURCH



For buildings in a terrace, rigid body tilting will lead to tearing at the junction with the neighbour unit.

GeoSS 10112009 41

148 RACE COURSE ROAD

GeoSS 10112009 42

148 RACE COURSE ROAD



Shirlaw, Wen, Algeo & Patterson-Kane (2003)

GeoSS 10112009 43

148 RACE COURSE ROAD

Settled by 107mm

No 146, piled



Building tilting away from the adjacent structure


GeoSS 10112009 44

148 RACE COURSE ROAD



GeoSS 10112009 45


148 RACE COURSE ROAD



Adjacent buildings on different foundations: Old buildings on footings butted against newer buildings on deep foundations.

GeoSS 10112009 46

148 RACE COURSE ROAD



Racking action causes damage, in particular at door / window frames / arches.

GeoSS 10112009 47


Masjid Wak Tanjong

GeoSS 10112009 48


Masjid Wak Tanjong



Masjid Wak Tanjong




Masjid Wak Tanjong



Interface between Kallang Formation and OA

GeoSS 10112009 51


Masjid Wak Tanjong



Typical
Excavation
Sequence


GeoSS 10112009 52

Masjid Wak Tanjong




GeoSS 10112009 53

Masjid Wak Tanjong




GeoSS 10112009 54

Masjid Wak Tanjong



GeoSS 10112009 55

Masjid Wak Tanjong



Lateral Soil Movement in Front of the Mosque



GeoSS 10112009 56

Masjid Wak Tanjong

- Max reduction in pore water pressure in piezometric level:
 - At 9m below ground: 1.5m
 - At 15m below ground level: 3m
 - 27m below ground level: 6m

GeoSS 10112009 57


Masjid Wak Tanjong



Building Settlements

GeoSS 10112009 58

Masjid Wak Tanjong




GeoSS 10112009 59

Masjid Wak Tanjong



GeoSS 10112009 60

Masjid Wak Tanjong




Part of the building on piles and part on footings –
Damaging at small differential settlements.

GeoSS 10112009 61


Other Examples

GeoSS 10112009 62




**Annex structure
on footings
abutting buildings
on piles**

GeoSS 10112009 63



GeoSS 10112009 64



STAR SINGSATION KTV CLUB



GeoSS 10112009 67

Walkway - piled

Main load bearing column - shallow foundations

The diagram shows a white rectangular box representing the column above two vertical lines representing the foundation. A blue arrow points from the text 'Main load bearing column - shallow foundations' to the base of the column in the photograph.

GeoSS 10112009 68

No 7 CANTONMENT ROAD



Shirlaw, Wen, Algeo & Patterson-Kane (2003)

GeoSS 10112009 69

No 7 CANTONMENT ROAD



Shirlaw, Wen, Algeo & Patterson-Kane (2003)

GeoSS 10112009 70

No 7 CANTONMENT ROAD



Shirlaw, Wen, Algeo & Patterson-Kane (2003)

GeoSS 10112009 71

Buildings over varying depths of soft clay - usually a terrace problem



Pocket of soft clay

GeoSS 10112009 72



GeoSS 10112009 73



GeoSS 10112009 74

POSSIBLE MEASURES

- To identify buildings that are unusually sensitive to settlement
- To carry out protective measures

GeoSS 10112009 75

IDENTIFICATION

- To identify buildings on mixed foundations -
A&A drawings
- To identify locations of variation in geology, in
particular along terrace houses
- A general walk around the site – building
inspection

GeoSS 10112009 76

IDENTIFICATION

- Look at the geological profile / soil investigation data - consolidation often associated with areas with soft clay (marine/estuarine)
- Sensitive buildings often show some signs of damage or repair - existing cracks / spalling
- Watch out for additions to old buildings or new buildings abutting old buildings
- With terrace houses, signs of local dips in the roof line, local settlements in the road outside or local damage to drains / aprons

GeoSS 10112009 77

PROTECTIVE MEASURES

- Recharge wells to control consolidation settlement (only fully works with nearly water-tight wall and with wells installed before excavation starts)
- Separate the parts of the structure on different foundations
- Prop (where necessary for safety) and repair afterwards
- Underpinning

GeoSS 10112009 78

CONCLUSIONS

- Methods of Mair, Taylor and Burland to be used.
- Stage 1 - if $< 10\text{mm}$, no need to consider further
- Stage 2 - 'green field' assessment. Assumes building is flexible and moves with ground
- Stage 3 - Detailed evaluation, taking into account building stiffness and foundations

GeoSS 10112009 79

CONCLUSIONS

- Buildings on mixed foundations are extremely sensitive to settlement and more susceptible to damage than other buildings.
- Stage 3 analysis for all buildings on mixed foundations are required.

GeoSS 10112009 80

THANKS

GeoSS 10112009 81